

Bluetooth/USB Mode

HID (Most Common)
(Human Interface Device)



SPP/VCP

(Serial Port Profile/Virtual COM Port)



Defaults

Reset



USB Data

Enabled



Disabled



2D Imager



Trigger Key

Feedback Buzzer

Feedback LED

Function Key

USB Connector (Data/Charging)

OPN3002n

Bluetooth Options

- **Bluetooth-HID** - This connection mode is the most common and is normally supported by host devices (computers, tablets and smartphones). Bluetooth-HID mode works as if a Bluetooth keyboard were attached to the host device. This means that all data scanned will be as if typed. It is important that there is a blinking cursor ready to accept your scanned data. Any text field is a valid place to scan a barcode.
- **Bluetooth-SPP** - This connection mode can be complicated and is only recommended for advanced users or users who have a dedicated application that manages connections to the scanner. It may also be necessary when pairing with host devices that do not support Bluetooth-HID mode (such as most older BlackBerry and Android devices). In this case, you may wish to download and install Opticon's wedge application (OpticonRL) from our website (see below).

Feedback Options

- **Vibrate Only** - The OPN3002n will vibrate only to alert the operator of a good scan.
- **Beeper Only** - The OPN3002n will beep only to alert the operator of a good scan.
- **Beeper & Vibrate** - The OPN3002n will both beep and vibrate to alert the operator of a good scan.

Bluetooth Disconnect / Reconnect

- When connected, a Bluetooth connection can be broken by holding the trigger key for 5 seconds. This will prolong battery life in some situations.
- When disconnected, a Bluetooth connection can be reestablished by holding the trigger key for 5 seconds. Barcode data stored when disconnected will be automatically transmitted.

More Information

North America

Worldwide

<http://www.opticonusa.com/start/opn>

<http://www.opticon.com/Data-Collectors.aspx>

USB Data Options

- **Enabled (Default)** - This feature allows the data stored on the OPN3002n to be transferred to an attached computer. Data is stored when the Bluetooth connection goes out of range or is otherwise interrupted. Stored data is automatically transmitted to the host device upon reestablishing the Bluetooth connection. The Bluetooth connection mode also determines the USB connection mode. Bluetooth-SPP will connect as USB-VCP (serial port) devices while Bluetooth-HID mode will result in an USB-HID (keyboard) connection. This USB setting also enables USB charging.
- **Disabled** - In this mode, the USB connector is used only to charge the OPN3002n.

iOS Keyboard Options

- **iOS On** - This mode is a companion mode to Bluetooth-HID and is intended for use with any Apple iOS device (iPhone, iPad and iPod) that has an on-screen keyboard. When this feature is enabled, the on-screen keyboard can be toggled on and off by use of the function key on the OPN3002n. The typical behavior for an iOS device is to hide the on-screen keyboard when a Bluetooth keyboard is paired (as the OPN3002n effectively is).

Feedback

Vibrate Only



Beeper Only



Beeper & Vibrate



iOS Keyboard Options

iOS On



Quick Start Instructions

Step 1 - Scan Bluetooth Mode

Scan the Bluetooth Default barcode that matches the connection method you wish to use, **HID** (recommended) or **SPP**.

If you are pairing with an Apple iOS device, you should now also scan the iOS ON barcode. This allows the on-screen keyboard to be toggled with the OPN3002n's function key.

Step 2 - Hold the Function Key for 5 Seconds

Hold the OPN3002n's function key for 5 seconds until it beeps and begins to flash blue. The OPN3002n is now discoverable by your host device. This can be cancelled at any time by holding the function key for another 5 seconds.

Step 3 - Perform Bluetooth Search on Host

Use the Bluetooth interface on your host device to search for and select the OPN3002n. The OPN3002n will beep to indicate success or failure. If you are pairing in Bluetooth-SPP mode, the OPN3002n will complete the pairing process as soon as you launch an appropriate application and open the serial port created by your Bluetooth software. If your host device does not support Simple Pairing, then you may use the barcodes at left to input a PIN code.

