




MDL-2001

Laser scanner

The MDL-2001 is a laser barcode scan engine with an extremely small form factor making it an ideal solution for integration into space-constrained devices. Featuring a visible laser diode that scans bi-directionally at a rate of 100 scans/second, scanning is fast, easy and reliable.



Highlights

- Features bi-directional scanning with a 650nm visible laser diode
- Extremely fast scan rate of 100 scans/second
- Small size makes it easy to mount and integrate into space constrained areas
- Connects via 12 pin FFC connector
- Low profile, square scan engine - dimensions of 20.4 x 11.2 x 18 mm and weight of 9.7 grams
- Engineering kit available - enables faster time to market
- Two year warranty

MDL-2001

Product Specifications



Communication

Serial CMOS: 12 pin FFC connector

Power

Voltage requirement: 3.3V \pm 10%

Current consumption: Max. 125 mA

Barcode scanner optics

Light source: 650 nm visible laser diode

Scan method: Bi-directional scanning

Scan rate: 100 scans / second

Reading pitch angle: \pm 35°

Reading skew angle: -50 to -8°, 8 to +50°

Reading tilt angle: \pm 20°

Curvature: R>15 mm (EAN8), R>20 mm (EAN13)

Min. resolution at pcs 0.9: 0.127 mm / 5 mil

Min. pcs value: 0.45

Depth of field at code 39:

70 - 650 mm (1.0 mm) / 2.76 - 25.59 in (39 mil)

50 - 420 mm (0.5 mm) / 1.97 - 16.54 in (20 mil)

50 - 260 mm (0.25 mm) / 1.97 - 10.24 in (10 mil)

50 - 150 mm (0.15 mm) / 1.97 - 5.91 in (6 mil)

60- 120 mm (0.127 mm) / 2.36 - 4.72 in (5 mil)

Supported symbologies

Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/
NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128
(EAN-128), GS1 Databar (RSS)(Exl. stacked), IATA,
Industrial 2of5, Interleaved 2of5, ISBN-ISSN-ISMN,
Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic,
UK/Plessey

Postal code: Chinese Post, Korean Postal Authority
code

Durability

Temperature in operation: -20 to 65 °C / -4 to 149 °F

Temperature in storage: -30 to 70 °C / -22 to 158 °F

Humidity in operation: 5 - 90% (non-condensing)

Humidity in storage: 5 - 90% (non-condensing)

Ambient light immunity: Fluorescent 4,000 lx max,
Sunlight 80,000 lx max, Incandescent 4,000 lx max

Drop test: Packed in dummy case 1.8 m / 6 ft drop onto
concrete surface

MTBF: 30,000 hours except laser diode (10,000 hours)
and except mirror scan unit (10,000 hours)

Physical

Dimensions (WxHxD): 20.4 x 11.2 x 18.0 mm /
0.80 x 0.44 x 0.71 in

Weight: Ca. 4.7 g / 0.17 oz

Regulatory & Safety

RoHS, JIS-C-6802 Class 2, FDA CDRH Class II

Items

Sold separately: MEK-3100 development board (With
power supply, RS232 cable, USB cable, PCBs)